

Pattern Repeat	18" W x 16.75" L
Width	144 (in)
Construction	Patterned Cut & Loop
Face Yarn	100% Ultron Nylon 6.6
Yarn Spec	Twisted and Superba Heatset with a minimum of 5.0 Turns per Inch
Treatments	Permanent Static Control, Commercial Carpet Protector & Stainguard Protection
* Tufted Yarn Weight	20 (oz)
** Tufts per Square Inch	104 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height	0.25 (in)
Primary Backing	5.5 oz. Multi layered woven and non woven composite for enhanced straightness, tuftbind and edge ravel.
Secondary Backing	Endura Loc™ High Performance backing system with 18 x 8 Lino Woven ActionBac; 10 yr. Warranty for delamination and edge ravel.
Post-Installation Protection	DO NOT USE PLASTIC. Plastic can permanently discolor carpet and cause accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Recommended Adhesive	Constantine's Premium Adhesive #29 for patterned and non-patterned carpet
Flammability	Passes Class 1 (ASTM E-648) Radiant Panel; Critical Radiant Flux >= .45 W/cm ² ; Smoke Density (ASTM E-662) < 450
Dye Lot Size	Unlimited
Custom Colors & Weight	Available at Minimum Yardages
Origin	U.S.A.
LEED	All products are available with varying percentages of post-industrial recycled fiber for a minimum of 2,500 sy. Recycled content percentages are determined by the total weight of the product and will be affected by the backing selection. We offer backings with post-industrial and post-consumer recycled content that can increase the total recycled content percentage. All recycled content contributes to the NC and CI LEED rating systems under Materials & Resources, Credit 4.1 Recycled Content, and Credit 4.2 Recycled Content. All of Constantine's™ recommended adhesives qualify as low-emitting adhesives and can contribute to LEED NC & LEED CI, EQ Credit 4.1, and LEED EB, MR Credits 3.1-3.2. All Constantine™ carpets meet CRI Green Label Plus testing and product requirements and can contribute to LEED NC & LEED CI, EQ Credit 4.3.
Warranty	10 Year Wear



* Tufted yarn weight is measured prior to tip shearing and is subject to post-shear weight variances.

** Constantine incorporates a patented, high density tufting process called multiple yarn infusion. Conventional measurements of gauge and stitch rate are inadequate and misleading. Therefore, tufts per square inch are used to provide accurate specifications.