

Composition	Organically grown, renewable granulated cork
Standard Size	12" x 12"
Thickness	3/16"
Finish	Prevarnished
Square Feet per Carton	90
Recommended Adhesive	#43 Cork Adhesive
ASTM E 648-97 Critical Radiant Flux	0.60 W/cm ² - Class 1
ASTM E 662-97 Smoke Density	75 (Passes) 450 or less
ASTM C 1028 Coefficient of Friction	0.67 (Exceeds ADA Standards)
AATCC 134 Electrostatic Propensity	Negative 0.5 kV
ASTM D 3884 Taber Abraser Test	0.08 grams (0.4%)
ASTM C 423-90a Noise Reduction Class	53
ASTM E 413-87 Sound Transmission Class	55
ASTM E 989-89 Impact Insulation Class	86.8
ISO 3810 Residual Indentation	< 2%
DIN 52612 Thermal Resistance	0.054 m ² -K/W (20°C)
Warranty	5 year (two additional finish coats required)
LEED	Cork is a rapidly renewable resource and qualifies as a contributing material in LEED-NC 2.1, LEED-CI 2 MR credit 6.1, and LEED-EB 2 MR credits 2.1-2.5. Constantine's Cork Contract Cement W-240 qualifies as a Low-Emitting Adhesive in LEED-NC 2.1, LEED-CI 2 EQ credit 4.1, and LEED-EB 2 MR credits 3.1-3.2.

