

<b>Composition</b>	Organically grown, renewable granulated cork
<b>Standard Size</b>	12" x 12"
<b>Thickness</b>	3/16"
<b>Finish</b>	Prevarnished
<b>Square Feet per Carton</b>	90
<b>Recommended Adhesive</b>	#43 Cork Adhesive
<b>ASTM E 648-97 Critical Radiant Flux</b>	0.60 W/cm <sup>2</sup> - Class 1
<b>ASTM E 662-97 Smoke Density</b>	75 (Passes) 450 or less
<b>ASTM C 1028 Coefficient of Friction</b>	0.67 (Exceeds ADA Standards)
<b>AATCC 134 Electrostatic Propensity</b>	Negative 0.5 kV
<b>ASTM D 3884 Taber Abraser Test</b>	0.08 grams (0.4%)
<b>ASTM C 423-90a Noise Reduction Class</b>	53
<b>ASTM E 413-87 Sound Transmission Class</b>	ASTM E 413-87 Sound Transmission Class
<b>ASTM E 989-89 Impact Insulation Class</b>	ASTM E 989-89 Impact Insulation Class
<b>ISO 3810 Residual Indentation</b>	< 2%
<b>DIN 52612 Thermal Resistance</b>	0.054 m <sup>2</sup> -K/W (20°C)
<b>Warranty</b>	5 year (two additional finish coats required)
<b>LEED</b>	Cork is a rapidly renewable resource and qualifies as a contributing material in LEED-NC 2.1, LEED-CI 2 MR credit 6.1, and LEED-EB 2 MR credits 2.1-2.5. Constantine's Cork Contract Cement W-240 qualifies as a Low-Emitting Adhesive in LEED-NC 2.1, LEED-CI 2 EQ credit 4.1, and LEED-EB 2 MR credits 3.1-3.2.

