

# C O N S T A N T I N E

## ***Environmentally Enhanced EPA 3 Specification***

---

<b>Backing Description</b>	EPA 3- Cushioned Backing
<b>Backing Compound</b>	Polyurethane <b>(contains 7-10% Rapidly Renewable material, 10-12% Post-consumer recycled content, and 45-50% Post-industrial recycled fly ash content)</b>
<b>Foam Coat</b>	.100"
<b>Delamination</b>	None (guaranteed)
<b>Tuftbind</b>	18-20 lbs.
<b>Edge Ravel</b>	None (Seam Sealer Required)
<b>Moisture Proof</b>	Moisture Resistant
<b>Flammability</b>	Passes Class 1
<b>LEED</b>	Recycled content percentages are determined by the total weight of the product and will be affected by the backing selection. Constantine's Environmentally Enhanced EPA 3 contains 10-12% post-consumer recycled content and 45-50% Post-industrial recycled content. All recycled content contributes to the NC and CI LEED rating systems under Materials & Resources, Credit 4.1 and 4.2 Recycled Content. This product contains a total of 7-10% Rapidly Renewable materials and contributes to the NC and CI LEED rating systems under Materials & Resources, Credit 6 Rapidly Renewable Materials.

CONSTANTINE COMMERCIAL

P.O. Box 2399 Dalton, GA 30722

mill 800.308.4344

# C O N S T A N T I N E

## ***Recycled PVC / Vinyl Backing Specification***

---

<b>Backing Description</b>	PVC / Vinyl Backing
<b>Backing Compound</b>	Closed Cell Vinyl (Contains 33% Post-Industrial Recycled Vinyl Material)
<b>Delamination</b>	None (guaranteed)
<b>Tuftbind</b>	18-20 lbs.
<b>Edge Ravel</b>	None (guaranteed)
<b>Moisture Proof</b>	Yes
<b>Flammability</b>	Passes Class 1
<b>LEED</b>	Recycled content percentages are determined by the total weight of the product and will be affected by the backing selection. Constantine's Vinyl backing is utilized on Constantine carpet tile and 6' goods and has 33% post-industrial recycled content that can increase the total recycled content percentage.

# C O N S T A N T I N E

## ***EPA 1 Backing Specification***

---

<b>Backing Description</b>	EPA 1- Unitary Backing
<b>Backing Compound</b>	Latex
<b>Delamination</b>	None (guaranteed)
<b>Tuftbind</b>	18-20 lbs.
<b>Edge Ravel</b>	None (guaranteed)
<b>Moisture Proof</b>	No
<b>Flammability</b>	Passes Class 1

### **LEED**

# C O N S T A N T I N E

## ***EPA 2 Backing Specification***

---

<b>Backing Description</b>	EPA 2- Non-Cushioned Laminate backing
<b>Backing Compound</b>	Polyurethane
<b>Delamination</b>	None (guaranteed)
<b>Tuftbind</b>	18-20 lbs.
<b>Edge Ravel</b>	None (Seam Sealer Preferred)
<b>Moisture Proof</b>	Yes ( Passes British Spill Test)
<b>Flammability</b>	Passes Class 1

## **LEED**