

C O N S T A N T I N E s p f 4 0 TM w a r r a n t y

Constantine provides a ten (10) year stain, lightfastness and ozone contaminant warranty on any Constantine carpet or modular tile treated with SPF 40TM.

This warranty applies to purchases of Constantine carpet for indoor commercial installation. This warranty is valid only if the carpet has been properly installed and maintained in accordance with Constantine's or the C.R.I.'s Installation and Maintenance Procedures.

This warranty applies to the original purchaser and is not transferable to subsequent owners of the carpet.

Constantine guarantees any product treated with SPF 40TM to meet the following stain, and fastness specifications for up to ten years.

Colorfastness to Crocking	AATCC 165-	No less than 5
Colorfastness to Water (hot & cold)	AATCC 107-	No less than 5
Colorfastness to Ozone	AATCC 129-	No less than 4
Colorfastness to Light	AATCC 16E-	No less than 4
Resistance to Soiling	AATCC 121-	No less than 4
Stain Resistance (Red Dye)	AATCC 175-	No less than 8.0

Constantine guarantees any carpet treated with SPF 40TM to resist stains up to ten years. AATCC test method 175 measures resistance to acid based stains and will serve as the approved test method under the guidelines of this warranty. Carpet treated with SPF 40TM will meet a minimum rating of 8.0 on the Red 40 stain scale.

Carpet treated with SPF 40TM is warranted to perform under a wide variety of commercial flooring applications. Proper usage and maintenance must be adhered to. If any portion of the carpet does not meet the warranty specifications as stated, Constantine will repair or replace the carpet in a commercially acceptable manner to conform to the warranty. In areas where furniture, equipment, work stations, etc. exist, moving costs associated with the replacement will be absorbed by the purchaser.

This warranty does not cover carpet improperly maintained or abused. Over wetting, harsh chemicals or heavy objects being dragged across the carpet are not warranted. Subfloors with excessive moisture (3.0 lbs. per 1,000 square feet) or slabs where pH levels exceed 9 will not be warranted.

All claims submitted under this warranty should be submitted in writing.

Constantine
PO Box 2399
Dalton, GA 30722
c/o Claims Dept.